



BY-PB25A / BY-PB30A / BY-PB40A

Aluminum Construction Boompole

The five-section telescoping aluminum boom pole provides a perfect solution for a wide range of occasions such as field production, live performance, filmmaking, etc. The boom pole is expandable and contractile. The ergonomic lock collar design makes it comfortable to handle for a long time. Featured with lightweight and rigid construction, allows it to be utilized even in the rigor conditions.

Supplied with a standard 3/8" and 1/4" threaded stud and a 1/4" to 5/8" screw adapter, the boompole is suitable for most shock mounts, stands, blimps. Furthermore, the aluminum boompole is built with captive-collet coupling system and it locks each section in place for even further reliability.

Highlights

- 3/8" and 1/4" threaded stud
- Supplied with a 1/4" to 5/8" screw adapter
- Lightweight and compact design
- Comfortable handle grip
- Velcro straps for cable management
- Twist locks

Specifications

Material:	Aluminum
Maximum Diameter:	φ41mm
Sections:	5
BY-PB25A:	Minimum Length: 26.9"(68.3cm)
	Maximum Length: 8.2'(250cm)
BY-PB30A:	Minimum Length: 30.8"(78.3cm)
	Maximum Length: 10'(300cm)
BY-PB40A:	Minimum Length: 38.7"(98.3cm)
	Maximum Length: 13.1'(400cm)
Weight:	BY-PB25A: 906g (31.9oz)
	BY-PB30A: 1078g (38oz)
	BY-PB40A: 1300g (45.8oz)

Compatibility

Adaptable for a variety of microphone shock mounts, stands, blimps.

www.boyamicro.com

SHENZHEN JIAYZ PHOTO INDUSTRIAL., LTD.
The BOYA logo is a trademark which is registered and owned by
Shenzhen Jiayz Photo Industrial., Ltd.
COPY RIGHT 2010-2020
Email: sales@boyamicro.com
www.boyamicro.com / www.jiayz.com

